



XP Line – Hydraulic Breakers – Light Range

Two-sided casing available - direct fit on the stick through pins and bushings



NEW

SMART VALVE
Plug & Play

3-YEAR WARRANTY
on your breaker



Technical Specifications		XP60	XP70	XP101	XP150	XP200	XP300	XP400
Working Weight	lb	132	187	220	353	510	660	950
Carrier Min / Max	lb	1,300 / 3,500	1,760 / 4,000	2,200 / 5,500	4,000 / 8,800	5,500 / 11,500	8,800 / 20,000	12,000 / 22,000
Total Height	in	37.80	41.30	43.20	49.60	54.60	57.10	63.80
Tool Diameter	in	1.50	1.65	1.65	2.20	2.50	3.15	3.15
Useful Length (Std Tool)	in	9.40	10.60	10.60	11.00	14.40	15.00	15.40
Working Pressure min / max	psi	1,450 - 1,595	1,595	1,450 - 1,595	1,740 - 1,885	1,595 - 1,885	1,595 - 1,885	1,740 - 2,030
Blows per Minute min / max	1/min	633 / 950	526	526 / 838	731 / 1,024	552 / 663	552 / 663	521 / 595
ENERGY CLASS	flb	130	150	250	350	650	700	1,100

*Promove reserves the right to modify the technical data without notice



XP Line – Hydraulic Breakers – Medium Range



Hour Meter
available on this line



Automatic Greasing System
available on this line



Technical Specifications		XP600	XP800	XP 1000	XP 1200	XP1500	XP1700	XP2000
Working Weight	lb	1,322	1,655	2,205	2,650	3,200	3,750	4,300
Carrier Min / Max	lb	15,400 / 28,600	20,000 / 33,000	26,500 / 39,700	30,900 / 44,100	35,300 / 55,100	41,900 / 61,800	48,500 / 64,000
Total Height	in	76.00	88.60	90.60	98.40	102.40	106.30	118.10
Tool Diameter	in	3.50	3.94	4.33	4.72	5.12	5.31	5.71
Useful Length (Std Tool)	in	19.50	20.50	21.70	21.70	22.40	26.40	26.60
Working Pressure min / max	psi	1,885 - 2,175	2,393 / 2,538	2,393 / 2,538	2,393 / 2,538	2,466 / 2,611	2,466 / 2,611	2,611 / 2,756
Blows per Minute min / max	1/min	370 / 550	538 / 720	339 / 718	339 / 718	332 / 593	371 / 932	307 / 523
ENERGY CLASS	flb	1,450	2,700	3,000	3,400	3,800	4,100	5,500

*Promove reserves the right to modify the technical data without notice



XP Line – Hydraulic Breakers – Heavy Range



Hour Meter
available on this line



Automatic Greasing System
available on this line



Technical Specifications		XP2400	XP3100	XP4500	XP7000
Working Weight	lb	5,180	6,810	9,650	15,210
Carrier Min / Max	lb	53,000 / 77,200	66,100 / 105,800	99,200 / 176,400	154,300 / 285,000
Total Height	in	126.00	137.80	149.60	165.40
Tool Diameter	in	5.91	6.30	7.09	8.27
Useful Length (Std Tool)	in	27.00	27.20	27.60	31.50
Working Pressure min / max	psi	2,611 / 2,756	2,611 / 2,756	2,611 / 2,756	2,611 / 2,756
Blows per Minute min / max	1/min	307 / 523	233 / 576	249 / 432	239 / 432
ENERGY CLASS	flb	6,000	9,700	12,500	16,500

*Promove reserves the right to modify the technical data without notice